

Model:KS8223

Smart POS Terminal

رهیاب رایان فردا
Rahyab Rayan Farda



Tablet POS Android

یک پایانه هوشمند قابل حمل با سیستم عامل اندروید، صفحه نمایش لمسی با رزولوشن بالا، چاپگر حرارتی سریع با شبکه WIFI/GPRS می باشد.

طیف گسترده ای از برنامه های کاربردی و چندمنظوره، جهت اجرا و پرداخت را می توان بر روی این پایانه فروشگاهی پیاده سازی نمود.



دفتر مرکزی: تهران، پردیس، پارک فناوری پردیس، خیابان نوآوری هفتم، پلاک ۷۱ کدپستی: ۱۶۵۷۱۶۳۸۷۱
دفتر فروش: تهران، بلوار آفریقا، بالاتر از چهار راه جهان کودک، ساختمان نگین (پلاک ۸۸)، طبقه اول، واحد ۱۰۵
تلفن: ۰۲۱-۸۸۸۷۸۷۳۱-۳ فکس: ۰۲۱-۸۸۸۷۸۷۳۴-۲۱ info@rahyabrayan.com www.rahyabrayan.com



KS8223

ویژگی های محصول :

- پردازشگر چهار هسته ای با کارایی بالا
- سیستم عامل اندرویدی با ورژن ۵/۱
- صفحه نمایش لمسی رنگی ۵/۵ اینچی با رزولوشن بالا
- ماژول بارکدخوان 1D/2D
- دارای باتری 5000MAH با طول عمر بالا

PRODUCT PARAMETER

Item	Specification
Processor	ARM Cortex A7, 1.1 GHz, 4 Core Processor
Memory	1GB DDR3 SDRAM, 8GB EMMC
System	Android 5.1
Magnetic card reader	Track 1/2/3, Bi-directional, ISO7810, ISO7811, ISO7813
Smart card reader	Supports 1.8V, 3.3V, 5V Card Supports Memory card, CPU card EMV L1 & L2, PBOC3.0, ISO7816 standard
Contactless card reader	13.56MHz, 1443 Type A/B Support mifare card and EMV contactless standard
SIM card slot	Support 1.8V and 3V
Mobile communication	Support 3G-4G, GSM, WCDMA, EVDO, TDSCDMA, TDD-LTE, FDD-LTE
BT	Support BT4.0 BLE
WIFI	Standard: 802.11b/g/n
GPS	Support built-in GPS and Beidou, GLONASS, Galileo system, LBS positioning
Audio	Support built-in speakers and audio play
LED	4 LED meet the Union pay contactless reader standard
Display	5.5" 1280x720 pixel, LCD, backlight control, signal strength, battery status Support multipoint capacitance touch, and touch operation
Printer	High-speed thermal printer, paper width: (57±0.5mm), paper length: 20m
Physical key	1 ON/OFF key, sound control key
Camera	Rear: Flash, auto-focus, 5 million pixels Front: 2 million pixels, support common one-dimensional barcode scanning
Port	1 Micro USB OTG interface, USB 2.0HS standard 1 SIM card slot 2 PSAM card slot 1 Micro SD card slot, supports up to 32GB
Power	input: 100-240VAC 50HZ; Output: 5V 24 2A DC; Micro-USB standard charging port
Battery	Long lasting lithium battery, 5000mAh, 3.7V
Environmental	Working temperature: -10°C ~ 50°C Relative humidity: 10%-90% (non-condensation) Storage temperature: -20°C ~ 80°C
Certification	PCI 4.x Contact EMV L1&L2 certification Contactless EMV L1 certification CCC certification Telecommunication equipment network access license Wireless transmitting equipment approval

